NPOWER
Power and automation technologies.

Perkins
Series Diesel Generator Sets

300 kVA - 400 kVA

ENGINE

- G-Drive Series heavy duty diesel engine
- 4 cycle, water cooled, turbocharged / turbocharged & air to air charge cooled
- Direct injection
- Mechanic / electronic governor system
- 12 / 24 volt self-starter and charger alternator
- Changeable air, fuel and oil filter
- Tropical type radiator
- Flexible fuel pipe
- Oil discharge valve and extention pipe
- Industrial type silencer, exhaust spiral or compensator
- Maintenance free battery
- Engine jacket water heater (In automatic models)
- Maintenance and operating instructions

ALTERNATOR

- Brushless, single bearing
- H Class insulation type
- IP21-23 Protection class
- Self exciter
- Automatic voltage regulator
- 2/3 Pitch factor windings
- 4 Poles

AUTOMATIC CONTROL PANEL

- LCD display screen
- Hardware and materials needed
- Battery charger
- USB port & RS-485 output

QUALITY STANDARD DIRECTIVES

- 2006/42/EC (Machinery Directive)
- 2014/30/EC (EMC Directive)
- 2014/35/EC (Low Voltage Directive)
- 2000/14/EC (Noise Emition Directive)

CANOPY / CONTAINER

- Modular type sound-proof canopy / container
- Easy installation type without welding canopy
- Epoxy and polyester powder painted canopy
- Canopy designed for easy maintenance
- Locakable doors on both sides of canopy
- Emergency stop button
- Transparent panel inspection window

PROTECTION & ALARMS

- High water temperature
- Low oil pressure
- High & low engine speed
- Low radiator water level
- Over current load
- High & low genset voltage
- Start / stop failure

OPTIONAL EQUIPMENTS

- Charge ampmeter
- Circuit breakers (In automatic models)
- Residental / Critical type silencer
- Sound-proof canopy or container
- Mobile trailer and truck installation
- Synchronization panel for 2-32 gensets
- 3 pole / 4 pole automatic transfer panel (A.T.S.)
- Fuel and oil heater
- Anticondensation heater
- Fuel automation systems
- Different IP and Insulation class alternator
- PMG

INTERNATIONAL QUALITY STANDARD

- EN12601, EN60204, EN12100, EN61000, EN55011
- TS ISO 8528, TS ISO 3744, TS ISO 3746, TS ISO 13857
- EN60034, EN55014, ISO 3046, BS5000, IEC 60034
- VDE 0530, BSE 4999, EN60335, IBC 2015:EC8 2004

Easy maintenance canopy design

Refilling from the outside of the canopy

Canopy made of galvanized steel

Warning system for decreasing fuel with electronic fuel level sender

NPOWER
Power and automation technologies.

Perkins

Series Diesel Generator Sets

	MODEL			N PR XX 0300	N PR XX 0330	N PR XX 0400
GROUP	GEN-SET POWER	STAND BY	kVA	300	330	400
			kW	240	264	320
		PRIME	kVA	275	300	350
			kW	220	240	280
	CANOPY DIMENSION (W x L x H) mm			1150 x 3820 x 2460	1150 x 3820 x 2460	1500 x 4400 x 2660
	CANOPY WEIGHT kg			2520	2670	3520
	OPEN DIMENSION (W x L x H) mm			1150 x 3340 x 1900	1150 x 3340 x 1900	1500 x 3600 x 2200
	OPEN WEIGHT			2220	2370	3010
ENGINE	BRAND			PERKINS	PERKINS	PERKINS
	TYPE			1506A-E88TAG4	1506A-E88TAG5	2206A - E13TAG2
	POWER	STAND BY	kW	267	293	349
		PRIME	kW	244	267	305
	SPEED (rpm)			1500	1500	1500
	CYCLE			4	4	4
	DISPLACEMENT (lt)			8,8	8,8	12,5
	NUMBER OF CYLNDERS			6 IN LINE	6 IN LINE	6 IN LINE
	BORE x STROKE (mm x mm)			112 x 149	112 x 149	130 x 157
	COMPRESSION RATIO			16,1 : 1	16,1 :1	16,3 : 1
	GOVERNOR TYPE			ELECTRONIC		
	INDUCTION			TURBOCHARGED - AIR TO AIR CHARGE COOLED		
	COMBUSTION SYSTEM			DIRECT INJECTION		
	COOLING SYSTEM			WATER		
	FUEL CONSUMPTION lt / h	%100 PRIME POWER		60,2	64,9	71,00
		%75 PRIME POWER		45,8	48,2	54,00
		%50 PRIME POWER		31,6	33,00	37,00
	TOTAL LUBRICATION SYSTEM CAPACITY (lt)			41	41	40
	TOTAL COOLANT CAPACITY (lt)			33,2	33,2	51,40
	FUEL TANK CAPACITY (lt)			585	585	970

Npower reserves the right to make changes in model, technical specifications, color, equipment & accessories without prior notice. All rights reserved.

Turkey Discover the potential